

SP-3 Grab Bar

Patent No. 7,373,694 B1

The SP-3 Grab Bar offers the best protection against falls among ligature resistant grab bars because it provides the most secure grip for patient support. It also has outstanding ligature resistance, including sloped flanges to guard against attachment left-to-right along the length of the grab bar. The SP-3 is suitable for use in showers and other wet environments. See our installation instructions for details about drainage.

We stock 12", 18", 24", 30", 36", 42", and 48" nominal lengths. Custom lengths are available from 6 inches to 12 feet.

Specifications

- **Dimensions:** Nominal length is center-to-center of mounting holes. (Graspable length = nominal - 1.25". Overall length = nominal + 3/4".) 5-1/4" height x 3-1/4" projection from wall.
- **Material:** 3/16" thick 6063 T6 AL grip area, welded 5/16" cast AL flanges
- **Finish:** 2 options
 - -SC: Silver powder coat with clear protective top coat
 - -WA: White antimicrobial powder coat
- **Codes/Standards:** ADA compliant
- **Installation:** Requires six 1/4"-20 security fasteners, not included. A center support bracket is included for grab bars longer than 4'. Designed for horizontal installation only.

Front View
(White Antimicrobial
Powder Coat)



Rear View
(Silver/Clear
Powder Coat)

