

SP-11 Lavatory

(Pat. 9,003,577 B2)

The SP-11 Lavatories offer the highest degree of safety, yet are also user-friendly and have a pleasant appearance. All of our lavatories offer multi-directional ligature resistance (front, left, and right sides). Two potential points of ligature are mitigated with our custom grid drains and use of sinks without overflows. All of our lavatories have fully enclosed plumbing. With our dial control option, the SP-11 is the only ligature resistant lavatory available that allows patients to mechanically control their water temperature. Other features include simple installation and easy access for maintenance via panels fastened in place with security screws.

The SP-11 Lavatories are custom built. Our projects have run the gamut from triple-sink units to the use of small sinks to fit in tight spaces. Options include ADA or standard configurations, free standing or wall-mounting, and push button or dial faucet controls. All plumbing meets lead free requirements. Please contact us with your requirements to receive a detailed proposal.

Specifications

- **Dimensions:** Per customer requirements (34" height x 21" depth typical)
- **Countertop / Backsplash/ Sidesplash (if applicable):**
 - *Material:* ½" thick Formica Solid Surface (Corian equivalent)
 - *Color:* White (unless otherwise specified)
- **Cabinet:**
 - *Material:* ¾" white CertainTeed PVC
 - *Configuration:* Standard or ADA
- **Sink:**
 - *Material:* Stainless steel, 20 gauge
 - *Dimensions:* 17-1/8" x 14" oval, 5-3/8" depth (typical)
 - *Installation:* Mounted under countertop
 - *Feature:* No overflow
 - *Code/Standard:* ASME A112.19.3/CSA B45.4
- **Grid Drain:**
 - *Material:* Plated brass
 - *Feature:* 3/32" diameter holes for enhanced ligature resistance (less than half the diameter of typical grid drains)
 - *Drainage:* Includes air gap for ample drainage flow rate





Ligature-Resistant Safety Products

- **Spout:**
 - *Material:* 304 stainless steel (ANSI/NSF 61 compliant)
 - *Aerator:*
 - 1.5 gpm (unless otherwise specified)
 - Vandal resistant, key included
 - ANSI/ASMI A112.18.1M, ANSI/NSF 61 certified
 - *Mounting:* Installed on sloped section of backsplash
- **Faucet Controls:**
 - *ADA Push Button*
 - Chrome plated push button handle
 - Recessed in custom stainless steel flanged collar
 - Adjustable cycle time
 - ASME A112.18.1M, NSF/ANSI 61
 - Temp pre-set w/ under counter ASSE 1070 thermostatic mixing valve
 - *Dial Hot / Cold (or Single Pre-Mixed)*
 - Tapered chrome plated cast bronze handle
 - Tapered chrome plated brass escutcheon plate
 - 90° Compression cartridge
 - ASME A112.18.1M, NSF/ANSI 61
- **Installation:** Free standing or wall mount. Faucet controls, sink, grid drain, and spout are pre-installed. Detailed instructions included with each order.
- **Maintenance:** All plumbing is concealed within the cabinet, accessible by removing security fasteners holding front PVC panel in place.

