

## SP-11GDK-L Lavatory Grid Drain Kit

Standard lavatory grid drains can be used as a point of ligature attachment by threading a string or lace through the holes of the grid. The SP-11GDK-L greatly reduces this hazard by utilizing holes less than half the diameter of the typical grid drain. Effective drainage is achieved with the included air vent. **This grid drain is not designed for use with lavatories with overflows. Overflows are a point of ligature.**

### Specifications

- **Grid Drain:**
  - Chrome plated brass
  - 2-1/4" OD
  - 3/32" Dia Holes
- **Other Components:**
  - Rubber washer, red fiber washer, brass locknut
  - 1-1/4 chrome plated brass elbow and offset tailpiece, 17 ga
  - Chrome plated cast brass slip joint tee 1-1/4" x 1-1/2" x 1-1/2"
  - 1-1/2" x 12" chrome plated brass waste bend, 22 ga
  - 1-1/2" x 8" chrome plated brass flanged tail piece, 22 ga
- - Air vent with float ball check
- **Operation:** Drainage flow rate exceeds 2.3 gpm with vent system
- **Installation:** Grid drain fits in standard 1-5/8" lavatory sink openings. The tee has 1-1/2" slip joint connection to P-trap (not included). Requires cutting of tubular brass components to fit the air vent under the sink. **Cannot be used with sinks with overflows.**

