

SP-7WC Quick Connect Hand Shower

The SP-7WC is comprised of an SP-7 Shower Head modified with a nozzle that accepts a quick-connect attachment for a hose and spray head (included). When the hose is disconnected, the sloped and tapered design of the SP-7WC impedes attempts to tie anything to it.

WARNING: The hand-held spray attachment is only intended for use under the supervision of facility staff. When not in use, the hose and spray head must be removed from the SP-7WC and stored in a secure location.

Specifications

- **Shower Head / Nozzle:**
 - *Dimensions:* 3-1/2" x 5-1/4" x 2-1/4" projection from wall
 - *Material:* Cast bronze, brass
 - *Finish:* Chrome plated
- **Hose:**
 - *Length:* 69" long nominal (92" extended)
 - *Material:* Stainless steel over rubber liner, brass fittings
 - *Standards:* ASME A112.18.1 / CSA B125.1
- **Hand-Held Spray:**
 - *Material:* White engineering grade plastic
 - *Flow Rate:* 1.75 GPM at 80 psi (also available in 1.5 GPM)
 - *Operation:*
 - Push button reduces flow to trickle
 - Integral backflow check valve
 - *Standards:* ASME A112.18.1 / CSA B125.1, ASME A112.18.3
- **Installation:** Front mounting with 1/2" female NPT inlet. 1/4-20 security fasteners not included.



Note: The SP-7WC is not designed for showering without the hose and spray attached.