

SP-7TC Twist Connect Hand Shower

The SP-7TC is a quick-connecting hand shower that is ligature-resistant when the hose and spray head are removed. The SP-7TC has a spring-check mechanism that reduces water flow to a drip/trickle unless the male adapter for the hand shower is fully connected. This prevents accidental flooding while the drip/trickle alerts the user if the shower valve is still turned on.

WARNING: The hand-held spray attachment is only intended for use under the supervision of facility staff. When not in use, the hose and spray head must be removed from the SP-7TC and stored in a secure location.

Specifications

- **Shower Head / Adapters:**
 - *Dimensions:* 3-1/2" x 5-1/4" x 2-1/4" projection from wall
 - *Materials:* Cast bronze, brass, stainless steel, PETG
 - *Finish:* Chrome plated (except PETG)
 - *Operation:* Spring check restricts flow of water unless male adapter is inserted
- **Hose:**
 - *Length:* 69" long nominal (92" extended)
 - *Material:* Stainless steel over rubber liner, brass fittings
 - *Standards:* ASME A112.18.1 / CSA B125.1
- **Hand-Held Spray:**
 - *Material:* White engineering grade plastic
 - *Flow Rate:* 1.75 GPM at 80 psi (also available in 1.5 GPM)
 - *Operation:*
 - Push button reduces flow to trickle
 - Integral backflow check valve
 - *Standards:* ASME A112.18.1 / CSA B125.1, ASME A112.18.3
- **Installation:** Front mounting with 1/2" female NPT inlet. 1/4-20 security fasteners not included.

